

**CHEVRON™**

**MEDIUM DUTY WRECKER  
MODEL 1014**



### STANDARD FEATURES

- Aluminum modular body sides with two tool compartments each side
- Aluminum 28 in. tunnel through box with tool compartment lights
- Tool compartment door closures on all doors
- 108, 120, 136 or 148 inch CA (must specify)
- 12,000 lb. Planetary winches
- 7/16 x 150 ft. cable
- Cable tensioners
- 2 inch forks
- 3 inch forks
- 4 inch forks
- Spring shackle adapters
- Low profile fork holders
- Underlift crossbar extensions
- Elevated fork holders
- Truck releasable L-arms
- Wheel straps and ratchets
- Tandem pump group
- Safety chain pockets
- Safety chains
- Slanted light pylon
- Electric wire remote control for underlift
- FMVSS 108 lighting
- Junction box with wire harness
- Pilot operated holding valves
- Lubrication fittings on all pivot points
- Dual rear controls
- Rear D-rings
- Tow light plug
- Backup alarm

### OPTIONAL FEATURES

- 15,000 lb. Planetary winches with air free spool release
- Hydraulic rear stabilizers
- Medium duty truck bar with chains
- J-hook chains
- PTO
- Trailer ball adapter
- Mudflaps
- Car releasable L-arms
- Glad Hand and seven pin connector
- Bar light
- Work lights
- Switch panel
- Magnetic tow lights
- Electric wire remote control for boom
- Pintle ball hitch adapter

### CHASSIS RECOMMENDATIONS

	1014
CA	108, 120, 136 or 148 inch
Minimum Tire Size	245/70R 22.5
Maximum Tire Size	11R 22.5 (42 in. diameter)
Minimum Frame Height	35 inches
Maximum Frame Height	41 inches
Minimum GVWR	25,950 lbs.
Maximum GVWR	33,000 lbs.
Minimum Frame RBM	850,000 in • lbs each rail

NOTE: Fuel tank position - back of fuel tank must be within 3 inches of back of cab.

### SPECIFICATIONS

Body width	96 inches
Boom elevation	35 degrees
Boom reach past tailboard	90 inches
Underlift reach from tail board to center of fork	72 inches
Power tilt range	+ 8 degrees and - 7 degrees
Control valve-boom	Sectional, 20 GPM, 2000 PSI
Control valve-underlift	Sectional, 12 GPM, 2000 PSI
Oil reservoir	20 gallons
Oil filters (2)	12 GPM, 10 Microns
Tandem Pump	15 GPM each port

RATINGS* (lbs.)	1014
BOOM: • Retracted • Extended	28,000 12,000
WINCH AND WIRE ROPE: • Warn Winch (1st layer) - Wire Rope Working Limit - Wire Rope Diameter - Standard Length  • DP Winch (1st layer) - Wire Rope Working Limit, 1/2 in. diameter - Wire Rope Working Limit, 9/16 in. diameter - Standard Length	15,000 4,700 7/16 inch 150 ft.  15,000 6,100 7,700 150 ft.
UNDERLIFT: • Retracted • Extended • Tilt Capacity (extended) • Tow Capacity (rolling) • Car L-arms (paired) (optional) • Truck L-arms (paired)	11,000 8,500 8,500 28,000 4,000 6,000

\* Load ratings are based on structural factors - not chassis capability or capacity.

*Chevron reserves the right to improve or upgrade its products without obligation to modify previously manufactured units. This publication is printed in the U.S.A. and is the exclusive property of Chevron, Inc.*



Distributed By:

Chevron, Inc.  
7320 W. Market Street • U.S. Route 62 • Mercer, PA 16137  
(724) 981-7500 • Toll Free (800) 886-6400 • FAX: (724) 981-4425  
www.chevroninc.com